

11 p x ts

Ans. 7

5

10

15

25

30

35

GR 99 P 4784

1a

a
global computer network (Internet), the electricity supply network and the broadband cable network - and any type of local area networks - for example the home automation system,

GR 99 P 4784

2

Al
cont

comprising a network with a radio transmission path, a PLC transmission path, an IRDA transmission path, an InstaBus transmission path, an HES Bus transmission path, a twisted pair transmission path or a coaxial cable transmission path.

According to the documents ?Funkschau [radio show] 3/1989, pages 45 and 46; Elektronik [electronics] 18/1995, pages 50 to 58; Elektronik [electronics] 17/1996, pages 42 to 47 and pages 48 to 53; Elektronik [electronics] 4/1997, pages 64 to 72; Elektronik [electronics] 1/1998, pages 30 to 33; Elektronik [electronics] 17/1998, pages 74 to 77, pages 78 to 81 and pages 82 to 84? the home automation system describes the technical management of buildings and dwellings. This covers everything that relates to the convenience of the occupant. This includes, for example, load and energy management, water heating, lighting, ventilation and heating systems, control of motor-driven elements (for example blinds, garage doors, roller shutters etc.) and safety and protection devices (for example smoke/fire alarms, intruder warning systems, access monitoring systems, motion indicators, etc.)

Furthermore, the term "technical management" also covers the control of any other electrical appliances, from adjusting a clock to switching on a coffee machine. For installation of home automation systems (building bus systems), the following preconditions must essentially be satisfied for successful market introduction:

1. No need for any additional wiring
2. Little cost involved
3. Uniform communication standard
4. Interoperability
5. Plug-and-Play capability

GR 99 P 4784

2a

*Al
crit!*

In the recent past, various standards for home bus systems have crystallized out in the field of home automation systems, based on different approaches (consumer-item orientated approach, installation-item

5 oriented approach,

GR 99 P 4784

3

*al
cont,*

computer-hardware-oriented approach) although, to a greater or lesser extent, these represent specific solutions for home automation. These standards include:

- 5 1. For the consumer-item-oriented approach, the Consumer Electronics Bus (CEBus), the ESPRIT Home System (EHS) and the Home Bus System (HBS),
2. for the installation-item-oriented approach, the Bati Bus, the European Installation Bus (EIB) and
- 10 the Smart House and
3. for the computer-hardware-oriented approach, the Local Operating Network (LON) and The Real Time Operating System Nucleus (TRON).

15 The question as to which of the standards that have been mentioned will in the end be adopted, and will thus become the de-facto standard, depends essentially on the attractiveness of the respective standard for home automation. However, such a system is attractive

20 and really useful only if there are a wide range of products which communicate via this network. Only if the house or dwelling occupier knows when he or she purchases a washing machine, an electric cooker etc. that the respective appliance will communicate with his

25 home bus system, will he or she perhaps be prepared to pay the additional costs for a home automation system, and to install such a system in his or her house. However, if the manufacturer of these appliances does not know which bus system will win the race in the end,

30 then this manufacturer will not in fact be prepared to invest in an expensive interface for the respective bus system in order subsequently to find that the appliances cannot in fact be sold any better as a result of this investment.

35

In order to improve the attractiveness of the home automation systems described above, an intelligent home interface (residential gateway) is therefore required

GR 99 P 4784

3a

*Al
cont*

which, firstly, is cost-effective and, secondly, offers
the manufacturer of appliances which can be remotely
controlled for

GR 99 P 4784

4

Al
cont

home automation purposes wide variation options for the implementation of the interfaces for the bus system that is used for home automation.

5 One approach for providing an "intelligent home interface" (residential gateway) as it is known from a German patent application entitled "Anordnung zum Ineinanderübersetzen von Protokolldateneinheiten inkompatibler Netze" [Arrangement for translation of
10 protocol data units of incompatible networks to one another] - official application file reference 19904544.5 - is to provide for translation of protocol data units of incompatible networks to one another, a telecommunications network - for example a public
15 telephone network (PSTN), the integrated service digital network (ISDN), the landline network based on the asynchronous digital subscriber line (ADSL), the mobile radio network based on the GSM Standard (first and second mobile radio generation), the mobile radio
20 network based on the UMTS Standard (third mobile radio generation), the mobile network based on the DECT and/or PHS Standard, the global computer network (Internet), the electrical power supply network and the broadband cable network - and a local area network -
25 for example in the form of a home automation system, comprising a network with a radio transmission path, a PLC transmission path, an IRDA transmission path, an InstaBus transmission path, an HES Bus transmission path, a twisted pair transmission path or a coaxial
30 cable transmission path - by means of a telecommunications terminal which is connected to the telecommunications network, has a remote control structure and is allocated to any given x interface for connection to the local network via a specific network
35 adapter.

GR 99 P 4784

4a

*Al
Cont'*

Owing to the increasing convergence of communications and information appliances, the telecommunications terminal in this case has the "intelligent interface" function ("gateway" function) added to it. The

5 information (for example control commands, status information, alarm messages, etc.) that needs to be transmitted for remote control of appliances in the local area network is transmitted from the interface in a specific record format, with a first record format

10 part which indicates the appliance identification and/or

GR 99-P 4784

5

the appliance address, a second record format part which contains the control command for the appliance, and a third record format part which contains the control payload information.

5

A telecommunications terminal designed in this way makes it possible to drive any appliances connected to that telecommunications terminal.

10 To do this, an operator has to use a remote control unit, for example just by transmitting the appliance identification and the control command, to initiate an action in the appliance defined by the appliance identification, to switch the appliance to a different
15 operating mode, or to check the current operating mode.

It is known for the output of the operating mode to be transmitted as a data word to the remote control unit, where it is generally produced in the form of an
20 alphanumeric output on a display on the remote control unit.

Furthermore, appliances are known which convert data words, which generally contain numerical values, by
25 means of a device for speech synthesis into the spoken corresponding form, which is produced as the output. For example, the value "0" is output as a spoken "zero".

30 The user of such appliances then generally has to use a list or a manual to determine the meaning of this value, that is to say, in particular, an appliance status associated with this value.

35 This type of appliance status output is very tedious for an operator and requires that this list or manual always be available, in order to control the appliance remotely.

October 30, 2001
199904784

6

DE0003297

Al
cont.

"XPRESS Reference Manual for the HCS II - Release 3.62"
October 3, 1998, CREATIVE CONTROL CONCEPTS XP002162174
discloses a "home automation system" appliance, which
5 is equipped as a single-board computer which can be
upgraded in modular form. The appliance allows the
domestic appliances to be controlled which are
connected to the single-board computer via network
modules, with voice outputs via a telephone line being
10 possible by means of a speech module and a telephone
interface module, when DTMF tones are entered.

The object on which the invention is based is to
specify a method for conversion of a voice output of
15 status messages, in particular in home automation
systems, which can be implemented cost-effectively and
easily and can be used universally for respectively
different network types (for example the types of
networks mentioned above).

20 This object is achieved by the features of patent claim
1.

In the method according to the invention - as claimed
25 in claim 1 - a unique appliance identification is
allocated to each appliance which is connected to a
telecommunications terminal and is thus included in a
local area network, by means of which the
telecommunications terminal can address the respective
30 appliance, in particular for remote control, and by
means of which each appliance is identified. Three
spoken phrases are allocated to each appliance
identification, and thus to each appliance, and are
stored in this association. Statuses which an
35 appliance, contained in the local area network, may
assume are taken by the telecommunications terminal
from the value of a data word which is transmitted to

AMENDED SHEET

October 30, 2001
199904784

DE0003297

6a

al
cont

the telecommunications terminal from that appliance. If the value of this data word corresponds to a first value, then the first spoken phrase associated with the appliance is selected as the output phrase. If the

5 value of the data word corresponds to a second value, then the second spoken phrase allocated to that appliance is selected as the output phrase. If the value of the data word corresponds neither to the first nor the second value, then the value of the data word

10 corresponds at least to a third value, and the third spoken phrase allocated to that appliance is selected, in conjunction with the third value, as the output phrase. If the output phrase is selected, it is converted to a form that is legible for a device for

15 speech synthesis, and is transmitted to this device for speech synthesis in order to be output.

GR 99 P 4784

7

al
cont'

The method according to the invention achieves greater user acceptance of a system provided in this way for remote control of appliances, in particular home automation systems, since the use of spoken phrases for outputting appliance statuses makes it easier for the user to understand the data word values, which are rather cryptic without any additional information. Furthermore, this also mostly avoids any need to refer to the appliance statuses that are associated with the values of the data word, so that the remote control, in particular the remote checking of the appliance status, can be initiated by the user without any major effort. Furthermore, restricting the spoken phrases associated with an appliance, in particular to three spoken phrases, together with the simplicity of the method, mean that the required memory space is minimal. The association of spoken phrases with appliance statuses can also be used universally for any given appliance.

20 An exemplary embodiment of the invention will be explained with reference to the single figure, which shows a flowchart of a method for converting a voice output of appliance statuses.

25 The figure uses a flowchart to describe the method for converting a voice output of appliance statuses.

At the start 1 of the method, which is carried out in a telecommunications terminal - especially in the background - so that the normal procedures in telecommunications terminals continue to be carried out without any disturbance, a check is first of all carried out to determine whether a new appliance has been connected to the telecommunications terminal.

35 If a new appliance has been connected, an appliance number ID is generated for that appliance, and is

GR 99 P 4784

7a

allocated uniquely to that appliance for appliance
identification.

*al
cont*

GR 99 P 4784

8

al
cont

The appliance number ID is generated such that a sequential number is allocated to the appliances. This means that the respective most recently allocated appliance number ID is incremented, and is allocated to the respective newly connected appliance.

As an alternative to this, it is possible to allocate to the appliance as the appliance identification an appliance number ID which is predetermined by that appliance and, after being connected to the telecommunications terminal, is transmitted to this telecommunications terminal during an initialization process.

A combination of alphabetic and numerical characters is also feasible for generating an appliance identification ID.

Once the appliance number ID has been allocated, the user is requested via a device which is associated with the telecommunications terminal, in particular a microphone, to enter a first spoken phrase SP1, which is allocated to an appliance status identified by a first value VALUE1, to specify a second spoken phrase SP2, which is allocated to a second appliance status identified by a second value VALUE2, and to specify a third spoken phrase SP3, which is allocated to any other appliance status, which is identified by a value VALUE3 which differs from the first and second values VALUE1, VALUE2.

If, for example, a remotely controllable roller shutter is connected to the telecommunications terminal, whose values that are identifying the statuses are defined in an interval [0; 255], with the value "0" corresponding to the "roller shutter entirely raised" status, and the value "255" corresponding to the "roller shutter entirely lowered" status, and with the other values

GR 99 P 4784

8a

*Al
cont*

identifying a status between these two statuses, then the user can speak the formulation "roller shutter entirely raised" as the first spoken phrase SP1, and allocate this to the value "0", and

GR 99 P 4784

9

al
cont'

the user can speak the formulation "roller shutter entirely lowered" as the second spoken phrase SP2 and can allocate this to the value "255". All other values which lie in the interval [1; 254] can be spoken by the user and associated with the formulation "the current position of the roller shutter corresponds to the value:". 5

Following the user check, the three spoken phrases SP1 to SP3 are stored in conjunction with the appliance number ID in the form of an organized list such that one, and only one, associated spoken phrase SP1, SP2, or SP3 can be determined by means of a current appliance number ID and a current value VALUE1, VALUE2 or VALUE3 identifying an appliance of state. 10 15

Alternatively, it is possible to provide for the spoken phrases SP1, SP2 and SP3 to be provided for each appliance such that they are already in digitized form, processed appropriately for storage and for speech synthesis, on a memory medium, for example a floppy disc or a memory chip in the appliance, so that they need not be entered by the user. 20

After the storage process, the method is started once again with a check as to whether a new appliance has been connected, at the startpoint 1. 25

If the check indicates that no new appliance has been connected, then a check is carried out in a second step 2 to determine whether an appliance status of some particular appliance, which is located in the local area network and is connected to the telecommunications terminal, is being queried by a user. 30

If this is the case, the appliance is requested to transmit a data word DW, which contains the value VALUE1, VALUE2 or VALUE3 of the current status of the 35

October 30, 2001

9a

al
cost

appliance. Once the data word DW has been received, a check is carried out to determine which of the values VALUE1, VALUE2 or VALUE3 is contained in the data word DW.

GR 99 P 4784

10

al
cont

If the data word DW contains the first value VALUE1, then the first spoken phrase SP1, which is associated with the appliance being checked, is set as the output phrase AP on the basis of the current appliance number ID and the current value VALUE1, VALUE2 or VALUE3 of the data word DW.

If the data word DW contains the second value VALUE2, then the second spoken phrase SP2, which is associated with the appliance being checked, is set as the output phrase AP on the basis of the current appliance number ID and the current value VALUE1, VALUE2 or VALUE3 of the data word DW.

For at least one third value VALUE3, which is not the same as the first value VALUE1 or the second value VALUE2, the spoken phrase SP1 which is associated with the appliance being checked is set, followed by the third value VALUE3, as the output phrase AP, on the basis of the current appliance number ID and the current value VALUE3 of the data word DW.

Once the spoken phrase has been defined, this is processed such that it can be transmitted and output by a device for speech synthesis.

If, for example, the user is checking the status of the roller shutters, then the formulation "roller shutter entirely raised" is output to the user if a transmitted data word DW contains the first value VALUE1 "0", the formulation "roller shutter entirely lowered" is output to the user for a transmitted data word DW whose second value is VALUE2 "255", and for every value ([1; 254]) which differs from this, for example a third value VALUE3 "23", the formulation "the current position of the roller shutter corresponds to the value: 23" is output to the user.

GR 99 P 4784

10a

*Al
cont.*

After each output, the method is finally continued from the startpoint 1.

GR 99 P 4784

11

al
cont

If the check finds that the user is not checking any appliance status of any appliance which is located in the local area network and is connected to the telecommunications terminal, then the method is

5 likewise continued at the startpoint 1.

The exemplary embodiments which have been mentioned represent only some of the embodiments which are possible by virtue of the invention. For example,

10 anyone skilled in the art in this field will be able to create a large number of further embodiments by means of advantageous modifications, without the character (essence) of the invention being changed in the process. These embodiments are likewise intended to be

15 covered by the invention.